




Automotive - High Speed - Power

Electronic Switch for micro interruptions



MICRO INTERRUPTIONS

Micro-Switch **TOE 9261**

Micro-Switch TOE 9261

Electronic switch for micro interruptions in supply and ground lines up to 100 A


The Micro-Switch TOE 9261 is the first choice for generating short interruptions in supply voltages and therefore ideally suitable for testing vehicle electrics according to standards.

Depending on the model, currents up to 100 A can be switched at a rated voltage of up to 60 V.

Special features

- Input voltage max. 60 V
- Output current TOE 9261-50 max. 50 A
- Output current TOE 9261-100 max. 100 A
- Rise / fall time < 500 ns
- Short-circuit-proof
- Switchable discharge of load circuit
- Interruption in supply and ground lines up to 50 A or 100 A
- Switchable buffering of input circuit
- 4 signal line switches
- Control with any signal generators (TTL level)

While testing vehicle electric power systems according to standards, it is necessary to momentarily interrupt supply voltages. Using the Micro-Switch TOE 9261, switching operations between < 10 µs and nearly unlimited duration are possible without problem.



Any voltage source of up to 60 V with appropriate current rating provides the supply voltage.

Using an external signal generator, the current flow can be interrupted using switch S 1. Discharging the load circuit is possible during the interruption of the load current by using another internal switch (S 2).

In addition, a configuration can be selected for interrupting the negative return line of the load (ground interruptions).

Four signal line switches (S 3–S 6) additionally enable precise switching and interruption of signal and control lines in any current flow direction. Control of these switches is synchronous with S 1.

Covered test standards

12 V vehicle electrics
BMW GS 95024-2-1
LV 124
Mercedes-Benz MBN 10615
Mercedes-Benz MBN LV 124-1
VW 80000-1
48 V vehicle electrics
BMW GS 95026
LV 148
VDA 320
VW 82148

Technical specifications

	TOE 9261-50	TOE 9261-100
Power switch		
Input voltage	max. 60 V	max. 60 V
Output current	max. 50 A	max. 100 A
Peak switch-on current	max. 300 A	max. 300 A
Rise time / fall time		
tr / tf @ 1 Ω / 100 Ω / 1 kΩ	< 0.5 µs / < 0.5 µs	< 0.5 µs / < 0.5 µs
Signal line switches		
Input voltage	max. ± 60 V	max. ± 60 V
Output current	max. ± 2 A	max. ± 2 A
Rise time / fall time		
tr / tf @ 1 Ω (V = 2 V)	< 2.5 µs / < 1.5 µs	< 2.5 µs / < 1.5 µs
tr / tf @ 1 kΩ	< 0.1 µs / < 6.5 µs	< 0.1 µs / < 6.5 µs
Control voltage (trigger)	TTL-level, max. ± 20 V	TTL-level, max. ± 20 V

Micro-Switch TOE 9261

General data

Supply voltage	90 – 264 V, 47 – 63 Hz
Power consumption	max. 35 VA
Operating temperature	0 °C to 40 °C
Storage temperature	-20 °C to 70 °C
Reference temperature	23 °C ± 1 °C
Cooling	Thermostatically-controlled fan
Overall dimensions (WxHxD)	224 x 103 x 348 mm
Rack mounting dimensions (WxHxD)	224 x 88 x 325 mm
19" system	½ 19", 2 HU
Weight	Approx. 4 kg
Enclosure	Metal

Ordering data

Micro-Switch	
TOE 9261-50	60 V / 50 A
TOE 9261-100	60 V / 100 A



Options / accessories

Micro-Switch	
TOE 9260/22	0.50 m cable with 1 safety socket, red
TOE 9260/23	0.50 m cable with 1 safety socket, blue
TOE 9260/24	1.20 m cable with 1 safety socket, red
TOE 9260/25	1.20 m cable with 1 safety socket, blue
TOE 9521	19" adapter 2 HU, for single installation
TOE 9522	19" adapter 2 HU, parallel installation set for 2 units
TOE 9260/100	Reference resistor unit 1 Ω, 100 Ω, 1k Ω

Supplied accessories

- 1 Instruction manual
- 2 Connector sockets for S3–S6



Our customers

AEG
A.M.S. Software GmbH
Alps Electric GmbH
artesy
ASKON
Atlas Elektronik
Audi

BASF AG
Bayer AG
Behr Hella Thermocontrol
Beiersdorf AG
BENDER
Beru AG
BIOMET
Blaupunkt
Boehringer Ingelheim KG
Boombardier
Robert Bosch GmbH
B. Braun Melsungen AG
Brose Fahrzeugteile
Bugatti Engineering GmbH
Busch-Jaeger GmbH
Bühler Motor

CERN
Continental AG

Daimler AG
John Deere
Degussa Hanau
DELPHI
DeltaTech Controls
DESY
Deutsche Lufthansa AG
Diehl Avionik Systeme
Diehl GmbH & Co.
DLR
DMT
Dornier Luftfahrt GmbH
Dräger
dSpace GmbH
Du pont

EADS
ebm-papst Gruppe
ELMOS
elster
Endress+Hauser
e-on
Eurocopter GmbH

FH Braunschweig/Wolfenbüttel
Fachhochschule Dortmund
Ferrari
FESTO
Fiat Automobile AG
Ford-Werke AG
Fraunhofer Gesellschaft
Karl Freudenberg
fuba
Fujitsu GmbH

Gidemeister Automation GmbH
GÖPEL electronic
Gossen-Metrawatt
Gould
GSI

Haas Laser GmbH
Hahn-Meitner-Institut
HARMAN/BECKER
Hauni Werke, Körber
Hella KG Hueck & Co.
Heraeus Sepatech GmbH
HIMA
HIRSCHMANN
Hochschule Furtwangen
Hoechst AG
Hoffmann-La Roche AG
Hüls AG

IAV GmbH
IBM Deutschland GmbH
iC Haus
Infineon AG
Iskratec

Jena-Optronik GmbH

Kabelmetal electro GmbH
Kathrein-Werke KG
KES
KMW
Knorr Bremse AG
KOSTAL
Krupp GmbH
KUHNIKE

Labom
Leica Camera GmbH
Ernst Leitz Wetzlar GmbH
Lenze
Linde
Lucas Automotive GmbH
Lufthansa Technik AG

MAN technologie
Maserati
MAXIMATOR
Max-Planck-Institute
Mercedes-Benz AG
E.Merck
Motorola
mtu

NOKIA

Opel AG
Osram GmbH

Pepperl + Fuchs GmbH
Philips GmbH
Phoenix Contact
PHOENIX TESTLAB
Pierburg GmbH
Dr. Ing. h.c.F. Porsche AG
preh
PTB

RAFI
Rank Xerox GmbH
Reis Robotics GmbH
Rexroth Bosch Group
Rheinmetall GmbH

Rockwell Automotive
Rohde & Schwarz
RUAG
RUB LEMS

H.-J. Schleißheimer
S&K Prüftechnik
SENNHEISER
SIEMENS
Skoda
ST Microelectronics GmbH
Stocko

Takati Petri AG
TU Darmstadt
Tektronix GmbH
theben
Thomas
Thyssen AG
TRW Automotive
TT electronics
TÜV-Rheinland
Tyco Electronics

Valeo GmbH
VDE
Vickers System GmbH
Voith Sulzer GmbH
Voith Turbo GmbH
Volkswagen AG

WACHENDORFF
Wacker Chemie GmbH
WAGO
Webasto
WEBER
Weidmüller
YAZAKI

ZF Antriebs- und
Fahrwerktechnik
Carl Zeiss
ZOLLNER